



SPORTS & LEISURE GRASS

**PRODUCT SPECIFICATIONS
 DOMO Foot 55 F**

Applications	Soccer, Rugby
--------------	---------------

Fibre	Polyethylene / UV-stabilized / Straight / Fibrillated 8800 dtex 12 mm ca 80 µm thickness
-------	---

Production Method	Linear tufting
Gauge	5/8"
# stitches / lm	110 / lm ± 10%
# tufts / m ²	6.929 / m ² ± 10%
# piles / m ²	13.860 / m ² ± 10%
Pile Height	55 mm ± 5%
Pile Weight	800 gr / m ² ± 10%
Total Height	57 mm ± 5%
Total Weight	1.864 gr / m ² ± 10%
Tuft Cloth	Polypropylene, UV-stabilized, 164 gr / m ² ± 5%
Backing	Latex, 900 gr / m ² ± 10%

Infill	Sand (ca. 15-20 kg, depending on subbase installed) (>80% roundness) Rubber (ca. 8-14 kg, depending on subbase installed)
--------	--

Roll Width	400 cm
Roll Length	As per lay-out

Colour	Green
Colour Lines	White / Yellow

Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 6.000 hours (DIN 53387)
Water Permeability	6.10 ⁻⁴ m/s
Inflammability	Class 1 with flame retardant EPDM infill (DIN 51960)
Pile Anchorage	> 30 N

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.